



5DA36451
Flat hood, 60 cm
Silver metallic

Output, consumption

- Energy efficiency class: A (on an energy efficiency class scale from A ++ to E)
- Average energy consumption: 19.5 kWh / year *
- Fan efficiency class: B *
- Lighting efficiency class: A *
- Grease filter efficiency class: C *
- noise min./max. Normal level: 53/59 dB
- Voltage: 220 - 240V
- Total connected load: 73 W
- Max. Capacity: 390 m³ / h

Equipment / comfort

- flat screen hood
- without handle (optional)
- For installation in 60 cm wide wall unit
- Optional extract air or recirculation mode
- For recirculation mode, a starter set is required
- Fan power 4-stage (3 power levels and 1 intensive level) controlled by short-stroke keys
- Intensive levels with automatic reset
- Automatic switching on and off when the movable filter surface is actuated
- Energy efficient operation through efficient BLDC technology
- Even, bright illumination with 1 x 3 W LED modules
- Illuminance: 489 lux
- Color temperature: 3500 K
- Metal grease filter, dishwasher safe

Technical data and dimensions

- Appliance dimensions(H/W/D): 203 x 598 x 290 mm
- Installation dimensions(H/W/D): 162 x 526 x 290 mm

Additional data

- Fan power according to EN 61591:
with exhaust air operation max. Normal level 260 m³ / h,
intensive level 390 m³ / h with recirculation mode max.
Normal level 160 m³ / h, intensive level 180 m³ / h
- Noise values according to EN 60704-3 and EN 60704-2-13
with exhaust air operation max. Normal level: 59 dB (A) re 1 pW
(47 dB (A) re 20 µPa sound pressure)
Intensive level: 69 dB (A) re 1 pW (57 dB (A) re 20 µPa sound pressure)
with recirculation mode max. Normal level:
70 dB (A) re 1 pW (58 dB (A) re 20 µPa sound pressure)
Intensive level: 72 dB (A) re 1 pW (60 dB (A) re 20 µPa sound pressure)

Accessories:

Features:

- Type: Excerpt
- Approval certificates: CE, VDE
- Length of connection cable (cm): 175
- Niche dimensions (mm): 162x 526x 290
- Net weight (kg): 7.8
- Control: electronic
- Max. Fan power exhaust air operation (m³ / h): 260
- Blower power for intensive stage recirculation mode: 180
- Max. Fan-circulating air operation (m³ / h): 160
- Blower power for intensive stage exhaust air operation (m³ / h): 390
- Number of lamps (pcs): 1
- Sound power (dB (A) re 1 pW): 59
- Diameter of exhaust air outlet (mm): 120/150
- Material of grease filter: aluminum
- Odor filter: no
- Type of air duct: convertible
- Delay shut off modes: 10M
- Optional accessories: 5Z5145X5, 5Z5760N0
- Type of lamps: LED
- Total power of lamps (W): 3
- Type of grease filter: cassette

Optional accessories:

- 5Z5145X5: Starter set for recirculation mode
- 5Z5760N0: Handle stainless steel








Consumption and connection values:

- Connected load (W): 73
- Hedging (A): 10
- Voltage (V): 220-240
- Frequency (Hz): 50; 60
- Plug type: Schuko / Gardy.m. grounding
- Type of installation: Integratable
- Housing material: galvanized
- Approval certificates: CE, VDE
- Plug type: Schuko / Gardy.m. grounding
- Dimensions of the packaged unit (in): 12.20 x 25.19 x 14.17
- Net weight (lbs): 17
- Gross weight (lbs): 21
- Position of the fan: motor in the housing
- Backflow flap: no
- Length of connection cable (cm): 175
- Dimensions of the device (mm): 203 x 598 x 290
- Dimensions of the packaged device (mm): 310 x 640 x 360
- Net weight (kg): 7.8
- Gross weight (kg): 9.0

Available color options:

- 5DA36451 : Flat hood

EAN-Nr.: 4251003102970



Size in mm