

Flat hood 60 cm 5DA36452 Stainless Steel

- Stainless Steel

 Power / Consumption

 Energy efficiency class: A

 Average energy consumption: 48.3 kW/year

 Fan efficiency class: A

 Lighting Efficiency Class: C

 Total connected load: 232 W

 Voltage: 220-2240 V

 Sound power (dB(A) re 1 pW): 62 dBA in Max

 Performance

 Power exhaust air operation (m3/h): 580

 Power intensive exhaust air operation (m3/h): 5

 Power recirculation mode (m3/h): 25

 Power in intensive air recirculation mode (m3/h): 3-

- Equipment / Comfort

 Fan capacity stepwise: 3

 Electromechanical control even, bright lighting with 2 LED lamps
 Illiuminance: 100 lux
 Colour temperature: 3000 K
 Cassette Filter

- Technical data and dimensions (HxWxD)

 Device dimensions exhaust air: 260 x 598 x 300-452 mm
 Device dimensions circulation: 260 x 598 x 300-452 mm
 Device dimensions (packed): 350 x 657 x 360 cm
 Net weight (kg): 9

 Gross weight (kg): 10



- Features:

 Device type: Flat screen cover

 Type: Built-in/extracted

 Approval certificates: CE

 Connection cable length (cm): 150

 Diameter of the exhaust air spigot (mm): 150

 Material of the grease filter: Aluminum

BLAUPUNKT

Special accessories:

Metal handle Charcoal filter Longlife charcoal filter 5Z5750NO 5Z9100X1 5Z9100X2

Available color options:

Consumption and connection values:

- Consumption and connection values:
 Connected load (W): 230
 Protection (A):
 Voltage (V): 20-240
 Frequency (Hz): 50
 Housing material: painted steel housing
 Approval certificates: CE
 Plug type: EU (earthed)
 Required distance from the hob:
 Electric hob: 450mm, Cas hob: 650mm
 Position of the blower: Motor in housing
 Flow direction: upwards

EAN-Nr.: 4251003105193



