



**Flat hood, 90 cm, silver metallic  
5DA39452**

**Design**

- Can be installed in 60 or 90 cm wide wall unit
- Optionally exhaust air or recirculated air operation
- For recirculation operation, a standard recirculation set (optional accessory) is required

**Design/Comfort**

- Electronic control on the side
- 4-stage fan power (3 power levels/ 1 intensive level) adjustable with short-stroke keys with LED display
- Intensive stages with automatic reset
- Automatic three-stage fan run-on with digital display

**Equipment**

- Bright illumination with 3 x 1,5W LED module
- Color temperature: 3500 K
- Illuminance: 355 lux
- Cassette with aluminum frame
- Metal grease filter, dishwasher safe

**Operating mode and power**

- Fan capacity for exhaust air operation according to EN 61591: max. normal stage 266 m³/h, intensive stage 412 m³/h
- Noise values according to EN 60704-2-13 for exhaust air operation:  
Max. Normal stage: 63 dB(A) re 1 pW  
Intensive stage: 70 dB(A) re 1 pW
- Noise values according to EN 60704-2-13 max. normal stage exhaust air operation: Noise, highest normal stage: 63 dB dB(A)
- Noise min./max. normal stage: 50/63 dB
- Energy-saving operation due to efficient BLDC technology

**Planning and installation information**

- Unit dimensions (HxWxD): 203 x 898 x 290 mm
- Installation dimensions (HxWxD): 162 x 526 x 290 mm
- Exhaust air connection Ø 150 mm (Ø 120 mm enclosed)
- Length of connection cable: 1.75 m with plug
- without handle (available as optional accessory)

**Environment and safety**

- Energy efficiency class: A (on an energy efficiency class scale from A+++ to D)
- Average energy consumption: 22.2 kWh/year\*
- Fan efficiency class: B\*
- Lighting efficiency class: A\*
- Grease filter efficiency class: C\*

**Special Accessories:**

- 5Z5145X5 : Standard recirculation set
- 5Z5790N0 : Stainless steel handle bar

**Equipment features:**

- Length connection cable: 175
- Niche dimensions (H x W x D): 162mm x 526.0mm x 290mm
- Height of the fireplace:
- Height of the device without fireplace:
- Control: electronic
- Type of lamps: LED
- type of plug: Schuko/Gardy.m. grounding
- Housing material: galvanized
- Approval certificates: CE, VDE
- Dimensions of the packed device: 12.20 x 37.00 x 14.17
- Net weight: 10.12 kg
- Gross weight: 12.30 kg
- Location of the blower: Motor in the housing
- Back pressure flap: No
- Length of connection cable: 175

**Consumption and connection values:**

- Connected load: 76 W
- Fuse protection: 10 A
- Voltage: 220-240 Volt
- frequency: 50, 60 Hz

EAN-Nr.:4251003106275

14-12-2021

