

5GB72290AU

60 cm, self-sufficient gas hob, stainless steel

- One-handed operated electric spark ignition
 Round front control knob
- pot carrier: cast iron

Performance and size:

- Performance and size:
 Connected load gas: 8,1 kW
 4 steplessly adjustable gas cooking plates
 1 strong, 2 normal, 1 economy burner
 Front left. Triple burner 1,0 kW
 Back left: Standard burner 3,5 kW
 Front right: Economy burner 1,75 kW
 Front right: Economy burner 1,75 kW

Environment and safety:
- Thermoelectric ignition fuse (protection against unintentional escape of gas)
- Preset to natural gas (20mbar)

Dimensions:

- Installation dimensions: (H/W/D) 45mm x 560mm x 490mm Device dimensions: (H/W/D) 90mm x 590mm x 510mm
- min. worktop thickness: 30mm Connecting cable 100cm

BLAUPUNKT

Features:
Type of appliance: Gas hob
Type: Built-in
Energy source: Gas
Number of cooking zones that can be used
simultaneously: 5
Control elements: round control knobs
Niche dimensions (mm): 45 x 560 x 480
Unit width (mm): 750

Dimensions (packed device mm): 818*574*166

Dimensions (packed device mm): 818*5
Net weight (kg): 14.47
Gross weight (kg): 16.85
Residual heat display: None
Control position: front
Type of control:
Main surface material: glass
Surface colour: black
Frame colour: glass
Approval certificates: CE/IAPMO+SAA

Length of connecting cable (cm): 100 Material control elements: plastic

Sealed hob: No Heaters with booster: Type of pot support: Cast iron

Available colour variations:

Special accessories:

. Nozzle set liquid gas

Accesories:
injector(For G31 27.5)
(R1 1/2) Elbow connector (Australia) + regulator
valve + pressure measuring connector (Australia
direction)
AD03 auxiliary pot holder (specially used in

Australia)

Consumption and connection values:

Consumption and connection values:
Power consumption (W): 2
Gas connected load (W): 111100
Fuse protection (A): Voltage (V): 220-240
Frequency (Hz): 50 - 60
Device colour: glass
Energy source: Gas
Type of gas: Natural gas G20 20mbar
Alternative gas type: Liquid gas G31 27.5mbar
Approval certificates: CE/IAPMO+SAA

Minimum distance from counter front (in): 50mm Minimum distance from rear wall (in): 65mm

EAN-Nr.: 4251003106503

CLEARANCES REQUIRED WHEN FITTING THE HOB WITH A COOKER HOOD ABOVE

