



**5GB61150**  
**60 cm, self-sufficient gas hob, stainless steel**

- Equipment:
- One-handed operated electric spark ignition
  - Round front control knob
  - pot carrier: cast iron
- Performance and size:
- Connected load gas: 8,1 kW
  - 4 steplessly adjustable gas cooking plates
  - 1 strong, 2 normal, 1 economy burner
  - Front left: Triple burner 1,0 kW
  - Back left: Standard burner 3,6 kW
  - Rear right: Standard burner 1,75 kW
  - Front right: Economy burner 1,75 kW
- Environment and safety:
- Thermoelectric ignition fuse (protection against unintentional escape of gas)
  - Preset to natural gas (20mbar)
- Dimensions:
- Installation dimensions: (H/W/D) 45mm x 560mm x 490mm
  - Device dimensions: (H/W/D) 90mm x 590mm x 510mm
  - min. worktop thickness: 30mm
  - Connecting cable 100cm

- Special accessories:**
- Nozzle set liquid gas



- Features:**
- Type of appliance: Gas hob
  - Type: Built-in
  - Energy source: Gas
  - Number of cooking zones that can be used simultaneously: 4
  - Control elements: round control knobs
  - Niche dimensions (mm): 45 x 560 x 490
  - Unit width (mm): 590
  - Dimensions (packed device mm): 180 x 678 x 590
  - Net weight (kg): 10,5
  - Gross weight (kg): 12,3
  - Residual heat display: None
  - Control position: front
  - Type of control:
  - Main surface material: stainless steel
  - Surface colour: stainless steel
  - Frame colour: Stainless steel
  - Approval certificates: CE
  - Length of connecting cable (cm): 100
  - Material control elements: plastic
  - Sealed hob: No
  - Heaters with booster:
  - Type of pot support: Cast iron

- Available colour variations:**
- 5GB62190 : Gas hob black glass

- Consumption and connection values:**
- Power consumption (W): 2
  - Gas connected load (W): 8100
  - Fuse protection (A): -
  - Voltage (V): 220-240
  - Frequency (Hz): 50 - 60
  - Device colour: Stainless steel
  - Energy source: Gas
  - Type of gas: Natural gas G20 20mbar
  - Alternative gas type: Liquid gas G30 50mbar OR G30,31 28-30/37mbar
  - Approval certificates: CE
  - Minimum distance from counter front (in): 50mm
  - Minimum distance from rear wall (in): 65mm

- Accessories:**
- injector(For G30)
  - hose couple(For G30)

EAN-Nr.:4251003103922

