



5GB71250
75 cm, Gas hob (self-sufficient), stainless steel

- Equipment:**
- One-handed operated electric spark ignition
 - Round front control knob
 - Cup support cast iron
- Performance and size:**
- Connected load gas: 11,1 kW
 - 5 burner burners
 - Front left: Economy burner 1 kW
 - Back left: Standard burner 3 kW
 - 1 wok burner 3,6 kW
 - Rear right: Heavy burner 1,75
 - Front right: Standard burner 1,75 kW
- Environment and safety:**
- Thermoelectric ignition fuse (protection against unintentional escape of gas)
 - Preset to natural gas (20mbar)
 - Can be converted to liquid gas
- Dimensions:**
- Installation dimensions: (H/W/D) 45 mm x 560 mm x 490 mm
 - Unit dimensions: (H/W/D) 90mm x 750 mm x 510 mm
 - min. worktop thickness: 30 mm
 - Connection cable: 100 cm

- optional extras:**
- Nozzle set liquid gas



- features:**
- Device type: Gas switch recess
 - Type: Built-in
 - Energy source: Gas
 - Number of cooking zones that can be used simultaneously: 5
 - Control elements: round control knobs
 - Niche dimensions (mm): 45 x 560 x 490
 - Unit width (mm): 750
 - Device dimensions (mm): 90 x 750 x 510
 - Dimensions (packed device mm): 188 x 833 x 598
 - Net weight (kg): 12,5
 - Gross weight (kg): 14,9
 - Residual heat display: None
 - Position of the control: Front
 - Type of control: Control knob
 - Main surface material: stainless steel
 - Surface colour: stainless steel
 - Frame colour: Stainless steel
 - Approval certificates: CE
 - Length of connecting cable (cm): 100
 - Material control elements: plastic
 - Sealed hob: No

- available colour variations:**
- 5GB72290 : Gas hob black glass, self-sufficient

- Consumption and connection values:**
- Power consumption (W): 2
 - Gas connected load (kW): 11.1
 - Fuse protection (A): -
 - Voltage (V): 220-240
 - Frequency (Hz): 50 - 60
 - Energy source: Gas
 - Type of gas: Natural gas G20 20 mbar
 - Alternative gas type: Liquid gas G30 50mbar OR G30,31 28-30/37mbar

- accessories:**
- injector(For G30)
 - hose couple(For G30)

- Minimum distance from counter front (in): 50mm
- Minimum distance from rear wall (in): 65mm

EAN-Nr.: 4251003103939

