



**5GB91250AU**  
**90 cm, Independent Gas Hob, stainless steel**

**Equipment:**

- One-handed operated electric spark ignition
- Round front control knob
- Cup support cast iron

**Performance and size:**

- Connected load gas: 11.1 kW
- 5 burner burners
- Front left: Economy burner 1 kW
- Back left: Standard burner 3 kW
- 1 wok burner 3.6 kW
- Rear right: Heavy burner 1.75
- Front right: Standard burner 1.75 kW

**Environment and safety:**

- Thermoelectric ignition fuse (protection against unintentional escape of gas)
- Preset to natural gas (10mbar)
- Can be converted to liquid gas(27.5mbar)

**Dimensions:**

- Installation dimensions: (H/W/D) 45 mm x 815 mm x 490 mm
- Unit dimensions: (H/W/D) 90mm x 860 mm x 510 mm
- min. worktop thickness: 30 mm
- Connection cable: 100 cm



**features:**

Device type: Gas hob  
 Type: Built-in  
 Energy source: Gas  
 Number of cooking zones that can be used simultaneously: 5  
 Control elements: round control knobs  
 Niche dimensions (mm): 45 x 815 x 490  
 Unit width (mm): 860  
 Device dimensions (mm): 90 x 860 x 510  
 Dimensions (packed device mm): 182 x 932 x 602  
 Net weight (kg): 14.0  
 Gross weight (kg): 17.0  
 Residual heat display: None  
 Position of the control: Front  
 Type of control: Control knob  
 Main surface material: stainless steel  
 Surface colour: stainless steel  
 Frame colour: Stainless steel  
 Approval certificates: CE, RCM  
 Length of connecting cable (cm): 100  
 Material control elements: plastic  
 Sealed hob: No

**Consumption and connection values:**

Power consumption (W): 2  
 Gas connected load (kW): 11.1 (39.96MJ/h)  
 Fuse protection (A): /  
 Voltage (V): 220-240  
 Frequency (Hz): 50-60  
 Energy source: Gas  
 Type of gas: Natural gas G20 10 mbar  
 Alternative gas type: Liquid gas G31 27.5mbar  
 Approval certificates: CE, RCM

Minimum distance from counter front (in): 50mm  
 Minimum distance from rear wall (in): 65mm

