

**Induction hob, 60 cm, Black
5IL64350**

Design:

- Frame design
- 60 cm width

Comfort:

- 4 Induction cooking zones
- 2 Combi zones
- Jog dial scroll display
- Combi Move
- PowerBoost function for all zones
- Electronic display
- Re Start function
- Quick Start Function
- Timer

Environment+safety:

- 2 stage residual heat indicator per cooking zone
- Main switch with stop-function
- Automatic pan recognition sensor
- Powermanagement function
- Safety switch-off
- Childproof lock
- Wipe protection function

Measurements:

- Installation dimensions: (ID/W/D) 55 mm x 560 mm x 490 mm
- Appliance dimensions: (W/D) 583 mm x 513 mm
- Min. worktop thickness: 20 mm
- Length connecting cable 110 cm
- connecting value 7400 W
- Cooking zones: 1 x Ø 190 mm, 210 mm, 2.2 KW (max. Power level 3.7 KW) Induction heating; 1 x Ø 190 mm, 210 mm, 2.2 KW (max. Power level 3.7 KW) Induction heating; 1 x Ø 190 mm, 210 mm, 2.2 KW (max. Power level 3.7 KW) Induction heating; 1 x Ø 190 mm, 210 mm, 2.2 KW (max. Power level 3.7 KW) Induction heating

Special accessories:

CZ9442X0 : Set of 3 pots and 1 pan

Features:

Product name/family: Cooking zone ceramic
Construction type: Built-in
Energy input: Electric
Total number of positions that can be used at the same time: 4
Type of control setting devices:
Required niche size for installation (HxWxD): 55 x 560-560 x 490-500
Width of the product (mm): 583
Dimensions of the product (mm): 55 x 583 x 513
Dimensions of the packed product (HxWxD) (mm): 126 x 753 x 608
Net weight (kg): 12.411
Gross weight (kg): 13.6
Residual heat indicator: Separate
Location of control panel: Hob front
Type of external control possibility:
Basic surface material: Ceramic
Color of surface: Black, Stainless steel
Color of frame: Stainless steel
Approval certificates: AENOR, CE
Length electrical supply cord (cm): 110
Knob Material:
Sealed Burners: No
heating with booster: All

Available colour variations:

5IL64350 : Induction hob, autarkic

Consumption and connection values:


Electrical connection rating (W): 7400
Gas connection rating (W):
Current (A):
Voltage (V): 220-240
Frequency (Hz): 50-60
Universal Product Code:
Main colour of product: Black
Energy input: Electric
Gas type:
Alternative gas type:
Approval certificates: AENOR, CE
Length of electrical supply cord (in):
Plug type: no plug
Required cutout/niche size for installation (in):
Minimum distance from counter front (in):
Minimum distance from rear wall (in):
Appliance Dimensions (h x w x d) (in): + x x
Dimensions of the packed product (in): 4.96 x 23.93 x 29.64
Net weight (lbs): 27
Gross weight (lbs): 30
Total number of positions that can be used at the same time: 4
Length electrical supply cord (cm): 110
Required niche size for installation (HxWxD): 55 x 560-560 x 490-500
Dimensions of the product (mm): 55 x 583 x 513
Dimensions of the packed product (HxWxD) (mm): 126 x 753 x 608
Net weight (kg): 12.411
Gross weight (kg): 13.6

Accessories:


EAN-Nr.:4251003103823

25-11-2019


measurements in mm




- A:** Minimum distance from the hob cut-out to the wall.
B: Recessed depth
C: With fitted oven underneath min. 30, possibly more; see space requirements for the oven.



Measurements in mm



Measurements in mm



① Ventilation gap must be present.

Measurements in mm