



5IX99290AU
Hob with integrated Extraction

Extractor fan

Output, consumption

- Voltage: 220 – 240 V
- Total connected load: 165 W
- Energy efficiency class: A+++
- Average power consumption: 30.8 kWh/year
- Fan efficiency class: A
- Grease filter efficiency class: B
- Noise min./max. Normal level/Intensive level: min. 45 dB(A) max. 65 dB(A) max. 70 dB(A)
- Fan output max. Normal level/ Intensive level*: in extraction mode 580 m³/h / 730 m³/h in circulation mode 450 m³/h / 560 m³/h

* According to EU Regulation No. 65/2014/ Fan capacity according to EN 61591

Equipment / comfort

- Electronic opening of the extractor fan
- Glass ceramic, black
- Suitable for installation in a kitchenette or kitchen island
- Optional extraction or circulation mode (carbon filter required for circulation mode)
- Fan output 6-level, controllable by touch control with 7-segment LED display
- 5 power levels + 1 intensive level
- Intensive level with automatic reset for extraction mode
- Automatic, three-level blower overrun of 5/10 and 20 minutes with LED display
- Metal grease filter and carbon filter saturation indication by LED control lamp
- To clean/evacuate the metal grease filter and the water collection tank, the appliance automatically blocks after 40 hours of operation
- Automatic overrun for circulation mode
- Water collection tank: 0.75 litre capacity
- Powerful and quiet blower
- Metal grease filter, dishwasher-safe
- Electronic opening of the extractor fan
- Glass ceramic, black
- Suitable for installation in a kitchenette or kitchen island
- Optional extraction or circulation mode (carbon filter required for circulation mode)
- Fan output 6-level, controllable by touch control with 7-segment LED display
- 5 power levels + 1 intensive level
- Intensive level with automatic reset for extraction mode
- Automatic, three-level blower overrun of 5/10 and 20 minutes with LED display
- Metal grease filter and carbon filter saturation indication by LED control lamp
- To clean/evacuate the metal grease filter and the water collection tank, the appliance automatically blocks after 40 hours of operation
- Automatic overrun for circulation mode
- Water collection tank: 0.75 litre capacity
- Powerful and quiet blower
- Metal grease filter, dishwasher-safe

Technical data and dimensions

- Appliance dimensions (H/W/D): 827 – 982 x 900 x 530 mm
- Installation dimensions (H/W/D): 58 x 8.2 x 495 mm

Features:

- Device type: Hob glass ceramic
- Type: built-in unit
- Energy Source: Electric
- Number of cooking zones used simultaneously can be: 4
- Device width (mm): 900
- Net weight (kg): 30.8
- Gross weight (kg): 39.65
- Residual heat indicator: Yes
- Location of the controller: Front
- Type of control: Touch control with 7 segment LED
- Display
- Main surface material: glass ceramic
- Surface color: black
- Frame color: No
- Approval certificates: CE, RCM
- Length of connection cable (cm): 150
- Heaters with booster: All 4

Consumption and connection values:

- Electric connection value (W): 7400
- Voltage (V): 220-240
- Frequency (Hz): 50; 60
- Device color: black
- Energy Source: Electric
- Approval certificates: CE, RCM
- Hob connector type: without plug

